



A Series Pallet Truck Basic Range

with capacities of 2,000kg

High Performance

- / AC travelling motor applied to provide excellent acceleration, good gradeability, low heat, no carbon brush and maintenance free.
- / The latest CURTIS AC control system provides accurate and stable control to work more efficient.
- / The applied CANBUS structure to offer more reliable and faster command access.
- / Regenerative brake and slope anti-slide function are offered by this truck.

Comfort

- / The shock absorption design of foldable platform improves comfort greatly to the operator.
- / Simple and beautiful tiller designed to operate all functions easily even by one hand.
- / Displayed turtle speed function applied to move slowly and helps to stack goods in narrow spaces.
- / Optimized designing structure to offer a good visibility and easy entrance of the pallet.
- / The compact body and big rounded design provide an ideal operation in limited space, and the wedge designed chassis greatly increases the passing ability.

Reliability

- / Five-pivot with low centre of gravity design and high strength steel frame structure chassis provide larger residual load capability and longer working life.
- / Water-proof plugs and connectors applied to provide a reliable protection to electric system.
- / The adopted unique floating suspension system ensures good driving wheels' grip and excellent stability.
- / Top quality hydraulic power unit applied to provide low noise, low vibration, smooth lifting and landing reliable operation.
- / Punch-formed forks to provide more strength and tip guide to provide higher efficient operation.
- / The power plug is fixed on the truck body to avoid damage from battery installment.

Safety

- / With three braking types: releasing brake, reversing brake and emergency brake, the driving safety has been ensured.
- / The applied slope anti-slip function ensures the safety of the operation.
- / The emergency button on the tiller head can effectively avoid the harm to the driver.
- / The standard equipped electronic lifting limitation and intellectual control limitation to offer double protection to working motor and loads from damaging.



Standard Specification

- | | |
|----------------------------|--|
| / Horn | / Hydraulic power unit |
| / Pedal (only CBD20-AEC1S) | / 540mm outside fork width |
| / AC drive wheel | / Electronic lifting limitation |
| / Tandem load wheels | / Emergency disconnect switch |
| / 1150mm fork length | / Multi-function battery indicator |
| / CURTIS AC controller | / CAN-bus system multi-function tiller |

Options

- / Load backrest
- / Guide roller of pallet
- / Handrail
- / 210Ah, 240Ah, battery
- / Different outside fork width (560mm, 600mm, 650mm, 680mm, 700mm)
- / Cold store protection (-30 C)
- / Different length of forks (1220mm, 1400mm, 1600mm, 2000mm, 2150mm, 2400mm)



Stand-on